

# DOUCET

## PMCT & PMCT-2 TRIANGULAR STROKE BELT SANDERS AND POLISHERS



Triangular Stroke Belt Sanders and Polishers **PMCT** and **PMCT-2**, have a fully welded structure. They feature dust hoods on both sides, a table with steel rollers and virtually wear free balanced and quiet running aluminum pulleys. All models are equipped with a magnetic starter (overload protection) and belt guards. Standard vertical adjustment is 24". Table weight capacity is 200 lb.

**The triangular shape allows better visibility on parts, better heat dissipation and belt saving.**


These sanders Polishers are ideal for Hairlining, Graining, to sand weld seams, for Polishing and to obtain a good mill finish. These models are also available in Dual Belt. Allow the user to operate with two different grits at one time.

Model	Table Size	Abrasive Belt	Motor / Voltage	Horizontal Adjustment	Overall (Length-Width-Height) +/- 1/8"
PMCT-284 PMCT-2-284	30" x 96"	6" x 284" 4750 ft./min.	5 HP 220-440-600	36 1/4"	139" x 77 1/2" x 87 3/8" 139" x 86 1/2" x 87 3/8"
PMCT-328 PMCT-2-328	30" x 120"	6" x 328" 4750 ft./min.	5 HP 220-440-600	36 1/4"	163" x 77 1/2" x 87 3/8" 163" x 86 1/2" x 87 3/8"
PMCT-374 PMCT-2-374	30" x 144"	6" x 374" 4750 ft./min.	7.5 HP 220-440-600	36 1/4"	187" x 77 1/2" x 87 3/8" 187" x 86 1/2" x 87 3/8"


PMCT-2 mean dual belt

## OPTIONS

- Contact wheel assembly with carriage
- Pneumatic tensioner
  - *recommended for applications with frequent changes of belt*
- Variable speed for 5 HP and 7.5 HP motors
- Single Phase 5 HP motor, 220 volts
- Single Phase 7.5 HP motor, 220 volts
- Enlarge the table from 30" to 48"
- Polishing Wheel
- Vacuum cup to hold parts, including:
  - 6 vacuum cups fixed to the table
  - 1 vacuum generator with manifold
  - 1 selector to start/stop vacuum



*Contact Wheel*



*Polishing Wheel*



*Pneumatic Belt Tensioner*



*Table with Vacuum Cups*

*To view video of this product,  
scan this QR Code  
with your mobile phone*

