


J-30

Multiple Spindle Vertical Boring Machine



**WITH HYDRAULIC POWER UNIT,
SUITABLE FOR AUTOMATIC FEED DEVICE**

DOUCET MACHINERIES INC.

ISO 9001

DOUCET




The J-30 Vertical Boring Machine is equipped with a fixed wooden table. Its vertical boring heads with spindles move up and down. Since its table is fixed, the machine can be equipped with an automatic feeding device.

As an option, the J-30 can be equipped with individual boring units mounted at one end of the table. Vertical spindle and hold downs can be mounted on individual arms or on a dovetail beam or a combination thereof. The boring depth and feed speed of the spindle carriage are widely adjustable.

The J-30 is available in 4, 5, 6, 8, or 10 foot width.

MODEL J-30		SPECIFICATIONS (4 foot model)	
BORING AREA		▶	24" by table length
TABLE (laminated hardwood)		▶	24" wide X 48" long
OPERATION		▶	single stroke
		▶	up to 8" stroke (adjustable)
		▶	3 HP hydraulic power unit
		▶	variable speed feed
SPINDLE MOUNT		▶	depending on drilling pattern and setup requirements, spindles can be mounted on individual cast iron arms, on a dovetail beam or into a machined aluminium template
SPINDLE(S)		▶	quantity as required
		▶	1½" in diameter with spring collet for ½" shank
		▶	speed 2300 RPM
		▶	timing belt driven
MOTOR(S)		▶	quantity as required (depends on the size of the machine)
		▶	1 HP, 208/220/440/575 volts, 3 Ph., 60 cycles
GUARD		▶	clear plastic guard
DIMENSIONS		▶	height 72", width 54", depth 52"
WEIGHT		▶	approximate net weight: 3000 lbs. - approximate shipping weight: 3250 lbs.



OPTIONAL FEATURES	
DIMENSIONS	▶ 48", 60", 72", 84", 96" or 120" machine and spindle beam width
SPINDLE	▶ 2" in diameter with spring collet for ½" shank
	▶ 1½" or 2" in diameter with Jacobs chuck ½" capacity
	▶ 1½" or 2" in diameter with set screw for ½" shank
	▶ 1½" or 2" in diameter for ¾" X 14 threaded shank
MOTOR	▶ 1.5, 2 HP, 208/220/440/575 volts, 3 Ph., 60 cycles
	▶ 110/220 volts single phase
HOLD DOWNS	▶ spring-loaded hold downs
IDLER	▶ pulley
TEMPLATE	▶ upon request
CLUSTER	▶ 2, 3, 4, 5 or more spindles or 32 mm center in line

Distributed by:

DOUCET MACHINERIES

ISO 9001

340, 6th Street
 Daveluyville, Quebec, Canada G0Z 1C0
 Tel. : (819) 367-2633 / Fax : (819) 367-2100
 info@doucetinc.com
 Visit our website at www.doucetinc.com